

RUBEROID[®] MODIFIED BASE SHEET*



Description

RUBEROID Modified Base Sheet is a premium, glass fiber reinforced, SBS modified base sheet.

Uses

RUBEROID Modified Base Sheet is designed for use in both mop applied modified bitumen and built-up roofing systems, as well as with all deck types. It may be mechanically attached to nailable decks, spot mopped to non-nailable decks, or solid mopped where appropriate. For new roofing and reroofing applications where long-term roof system performance is required.

Advantages

- Guarantees are available for up to 20 years.
- SBS modifier provides flexibility for easy installation.
- Resists wrinkling when installed.
- Rolls out flat for easy installation.
- Will not rot, curl, or shrink.
- Dimensionally stable for improved membrane performance.
- Durable—specially formulated SBS modified asphalt gives RUBEROID Modified Base Sheet lasting performance.

Advantages (continued)

- RUBEROID Modified Base Sheet is backed by GAF Materials Corporation, a company with over 100 years in the roofing business.

Applicable Standards

- UL Approved for use in the construction of Class A, B, or C roofs (Type G2 BUR).
- ASTM D-4601, Type II

Product Data (Approximate)

| | |
|------------------------|------------------|
| Roll Size..... | 39.4" x 97.5' |
| | (1.0m x 29.7m) |
| Coverage Per Roll..... | 3 squares |
| Roll Weight | 67 lbs (30.4 kg) |

*Not available in all areas.

